

REINFORCED BACK MOORING BITT
Ø 100 MM

ACCESS STEP

REAR BENCH
WITH DOUBLE LOCKER

NON-SKID EVA PROTECTION
ON THE SELF-DRAINING DECK

SAFETY HANDRAIL

POLYUREA PROTECTION - 15CM


ALUMINUM BOLSTER SEAT

ALUMINUM CONSOLE WITH FRONT SEAT

REINFORCED FRONT MOORING BITT
Ø 100 MM

ANCHOR LOCKER

FUEL TANK 90L



GENERAL ARRANGEMENT

PILOT 560



MAIN FEATURE PILOT 560	
LENGTH OVERALL	5.60 m
INTERIOR LENGTH	5.45 m
MAX WIDTH	2.30 m
INTERIOR WIDTH	2.00 m
DEPTH	1.20 m
PROTECTION THICKNESS	15 cm
NUMBER OF AIRTIGHT CHAMBERS	FULL POLYUREA
NAVIGATION CATEGORY	4th
DESIGN CATEGORY	C
HULL WEIGHT	410 kg
MAX LOAD	1200 kg
MAX NUMBER OF PASSENGERS	8
MAX MOTORIZATION	140 HP
Shaft	Simple L
FUEL TANK	90 L

OUTBOARD ENGINE SPECIFICATIONS		
MAX POWER	HP: 140	KW: 104
	KG: 188	LB: 415
MAX WEIGHT	L	
	140 HP	
SHAFT	INCLUDED CAPACITY	
FUEL TANK	90 L	

<p>x08</p>	
KG	LB
1306	2879

KG	LB
410	903

<p>FULL POLYUREA</p>	
----------------------	--

ALUMINUM HULL
POLYUREA PROTECTION
FRENCH DIVISION 222 BUREAU VERITAS NR600 STRUCTURE CERTIFICATION
CE
For more info : www.3dtender.com

This plan is the property of Samy BOUBEZARI, naval architect. It may not be used for construction, sold, reproduced or communicated to third parties without authorization. Law of 01.07.1992

Specification subject to change without notice. Tolerances dimensions and weight (±)10%