



GENERAL ARRANGEMENT

NIVIDIC 550



MAIN FEATURE PATROL 860	
LENGTH OVERALL	5.50 m
INTERIOR LENGTH	4.20 m
MAX WIDTH	2.40 m
INTERIOR WIDTH	1.32 m
DEPTH	1.17 m
TUBE DIAMETER	52 cm
NUMBER OF AIRTIGHT CHAMBERS	6
DEAD RISE TRANSOM	21°
DESIGN CATEGORY	C
HULL WEIGHT	400 kg
MAX LOAD	1350 kg
MAX NUMBER OF PASSENGERS	12
MAX MOTORIZATION	100 HP
Shaft	Simple L
FUEL TANK	50 L

OUTBOARD ENGINE SPECIFICATIONS		
MAX POWER	HP	KW
	100	73.6
MAX WEIGHT	KG	LB
	152	335
SHAFT	100 HP	
	INCLUDED	CAPACITY
FUEL TANK	70 L	

<p>x 12</p>	
KG	LB
1350	2976

KG	LB
400	882

AIR CHAMBERS : 6	

ALUMINUM HULL
TUBE INFLATION PRESSURE 0.25 BAR
ISO 6185 - C
CE
For more info : www.3dtender.com

This plan is the property of Samy BOUBEZARI, naval architect. It may not be used for construction, sold, reproduced or communicated to third parties without authorization. Law of 01.07.1992

Specification subject to change without notice. Tolerances dimensions and weight (±)10%